






Multiflex 20

Series-resistive 2-conductor with screen


Usage

For both indoor and outdoor placement
Laid in levelling compound or embedded into concrete

 Cable  80-160 W/m²  20 W/m

- ✓ Wide range of uses
- ✓ Classified M2
- ✓ UV-resistant


Multiflex 20 is a heating cable that is suitable for both indoor and outdoor installation and thus has a wide range of uses. The package includes cable on reel, warning sign and a practical reel bracket.

 Produkten bedömd i
SundaHus

Specifications

Connection voltage	230 V
Length Connection cable	2,5 m
Number of conductors	2 pcs
Bending radius, min.	30 mm
Diameter	5 mm
Output	20 W/m
Installation temperature, min.	-5 °C
Insulation material intermediate	Fibreglass yarn (410 TEX)
Insulation material inner	ETFE
Insulation material outer	PVC
Cable type	Series-resistive 2-conductor with screen
Enclosure class	IP67
Mechanical classification	M2
Protective conductor	Aluminium foil
UV resistance	Yes

Documents

 [CE document](#)

 [Manual](#)

Warranty



12 year product guarantee in case of material defects. The thermostat in the kit has a 5-year product guarantee. The guarantee period for the underfloor heating is extended to 25 years if the installation is carried out by an authorised

electrician and documented in Ebeco's Garantera service.

Our warranty terms

Article list

Article number	Resistance (Ω /km)
1	2 x 13
2	2 x 7
3	2 x 4,5
4	2 x 2,6
5	2 x 1,8
6	2 x 1,3
7	2 x 1
8	2 x 0,9
9	2 x 0,7
10	2 x 0,55
11	2 x 0,45
12	2 x 0,32

Supplementary products

EB Therm 500

EB-Therm 500



EB-Therm 800

Limstavar

Hot glue sticks

Learn more about this product:

<https://www.ebeco.com/products/underfloor-heating/multiflex-20>