




Cable ties



- Cable ties are made from high-quality Nylon (Polyamide 6.6)
- Good resistance to bases, oils, greases, oil derivatives, chloride solvents.
- Working temperature: -40°C~85°C
- Black colour - UV resistant

L - Length
W - Width
D - Bundle diameter

| Product name | Index | Colour | Dimensions | | Minimum bundle diameter [mm] | Maximum bundle diameter [mm] | Minimum tensile strength [N] |
|-------------------|-----------------|---------|-------------|------------|------------------------------|------------------------------|------------------------------|
| | | | Length [mm] | Width [mm] | | | |
| Cable tie 100x2.5 | CT-PA-100/2.5-N | Neutral | 100±3 | 2.5±0.2 | 3.00 | 20.50 | 80 |
| Cable tie 150x3.6 | CT-PA-150/3.6-N | Neutral | 150±3 | 3.6±0.2 | 3.50 | 36.00 | 180 |
| Cable tie 200x4.8 | CT-PA-200/4.8-N | Neutral | 200±3 | 4.8±0.2 | 3.50 | 49.50 | 230 |
| Cable tie 200x4.8 | CT-PA-200/4.8-B | Black | 200±3 | 4.8±0.2 | 3.50 | 49.50 | 230 |
| Cable tie 250x4.8 | CT-PA-250/4.8-N | Neutral | 250±3 | 4.8±0.2 | 3.50 | 65.00 | 230 |
| Cable tie 250x4.8 | CT-PA-250/4.8-B | Black | 250±3 | 4.8±0.2 | 3.50 | 65.00 | 230 |
| Cable tie 300x4.8 | CT-PA-300/4.8-N | Neutral | 300±3 | 4.8±0.2 | 3.50 | 81.00 | 230 |
| Cable tie 300x4.8 | CT-PA-300/4.8-B | Black | 300±3 | 4.8±0.2 | 3.50 | 81.00 | 230 |
| Cable tie 380x7.6 | CT-PA-380/7.6-N | Neutral | 380±5 | 7.6±0.3 | 8.50 | 108.00 | 540 |
| Cable tie 380x7.6 | CT-PA-380/7.6-B | Black | 380±5 | 7.6±0.3 | 8.50 | 108.00 | 540 |
| Cable tie 550x9.0 | CT-PA-550/9.0-N | Neutral | 550±6 | 8.8±0.4 | 8.50 | 163.50 | 800 |
| Cable tie 550x9.0 | CT-PA-550/9.0-B | Black | 550±6 | 8.8±0.4 | 8.50 | 163.50 | 800 |

RoHS

LVD

