Product data sheet Characteristics

ISM50320

OptiLine 45 - screeded floor box - without modules



Main	
Cabling installation system	Floor box
Product type	Screeded floor box
Type of floor	Screeded floor
Floor box shape	Square
Colour	Light grey
Quantity package 1 / unit	1 piece

Complementary

Fixing mode	Cast-in	
Number of modules	Without modules	
Product material	PP (polypropylene)	
Length	188 mm	
Height	7595 mm	
Width	188 mm	

Environment

Standards	73/23/EEC 93/68/EEC IEC 61084-1:ed. 1, 1991 IEC 61084-2-2:2003	
Operating temperature	-2560 °C	
IP degree of protection	IP20	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.5 cm
Package 1 Width	22.5 cm
Package 1 Length	23.0 cm
Package 1 Weight	648.0 g
Unit Type of Package 2	P12
Number of Units in Package 2	150
Package 2 Height	112.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	109.2 kg

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty	18 months	