

Product data sheet

Specifications



Mureva lights, Floodlight 150W, IP65 230V

IMT47222

Main

Range	Mureva
Range of product	Mureva lights
Product name	Floodlight
Product or component type	Lamp
Device application	Ware-houses and parking garages Residential Media device support Public areas Secure lighting Stadiums and arenas

Complementary

Type of installation	Outdoor
Total system power	150 W
Light source	LED
[Ue] rated operational voltage	230 V AC
Power factor	0.9
Colour rendering index	Ra=80
Luminous flux	18000 lm
Bulb lifespan	50000 h
Colour temperature	6500 K
Colour tint	Black
Provided equipment	Sensor
Electrical insulation class	Class E
Beam angle	110 °
Shape	Rectangular
Height	342.0 mm
Width	278.0 mm
Depth	61.0 mm
Net weight	4.05 kg

Environment

Environmental characteristic	Weatherproof
IP degree of protection	IP65
IK degree of protection	IK06
Ambient air temperature for operation	-30...45 °C

Packing Units

Unit Type of Package 1	PCE
Package 1 Length	40.0 cm
Number of Units in Package 1	1
Package 3 Width	40.0 cm
Package 3 Weight	10.518 kg
Package 2 Width	80.0 cm
Package 2 Height	75.0 cm
Package 2 Weight	96.144 kg
Number of Units in Package 3	2
Unit Type of Package 3	S04
Package 3 Height	30.0 cm
Package 3 Length	60.0 cm
Package 1 Width	32.4 cm
Package 1 Height	11.0 cm
Package 1 Weight	4.542 kg
Number of Units in Package 2	16
Unit Type of Package 2	P12
Package 2 Length	120.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	5 years
----------	---------