



EEN100

IP20

## Twilight switch 1 channel, 1M, wall mounted cell

### Technical characteristics

#### Architecture

Fixing mode	Din-Rail
-------------	----------

#### Main electrical features

Rated operational voltage Ue	230 V
------------------------------	-------

Frequency	50/60 Hz
-----------	----------

#### Electric current

Acceptable current rating with AC1	10 A
------------------------------------	------

#### Dimensions

Depth of installed product	65 mm
----------------------------	-------

Height of installed product	83 mm
-----------------------------	-------

Length	60 mm
--------	-------

Width of installed product	17,8 mm
----------------------------	---------

#### Length

Maximum connection distance between receiver and transmitter	100m
--	------

#### Power

Max. power with fluo uncompensated lamps	1000 VA
--	---------

Power consumed	0,331 VA
----------------	----------

Power consumption (operation)	300 mW
-------------------------------	--------

Incandescent bulb power	2300 W
-------------------------	--------

Total power loss under IN	0,3 W
---------------------------	-------

Power dissipation per coil	0,3 W
----------------------------	-------

#### Endurance

Electrical endurance cycles with incandescent lighting	7500
--	------

#### Capacity

Breaking capacity	10A 250V AC1
-------------------	--------------

#### Capacity

Number of modules	1
-------------------	---

#### Power supply

Supply voltage	230 V
----------------	-------

#### Lighting control

Brightness measurement range	5 / 2000 Lux
------------------------------	--------------

#### Fluorescent bulbs control

Max. power with fluorescent parallel lamps	1000 VA
--	---------

Max. power fluo. duo lamp comp. series	1000 W
--	--------

#### Incandescent bulbs control

Max. power with incandescent lamps	2300 W
------------------------------------	--------

<b>Installation, mounting</b>	
Mounting type	din-Rail
<b>Connection</b>	
Connection cross-sect. flexible conductor	1,5 / 6mm <sup>2</sup>
Connection cross-sect. rigid cable	1,5 / 6mm <sup>2</sup>
Number of contacts	1
Type of contacts	contact floating
Type of connection	with screw terminals
<b>Settings</b>	
Setting	Switch-on/switch-off delay continuously adjustable via potentiometer
<b>Safety</b>	
Protection index IP	IP20
<b>Use conditions</b>	
Operating temperature	-5...45 °C