

Produkta datu lapa

Specifikācijas



Motion sensor with push button integrated and relay, Renova, white

WDE011652

Galvenā

Product brand	Schneider Electric
Range	Renova
Produkta vai sastāvdaļas veids	Movement detector
Device presentation	Mechanism with fixing frame
Sensor type	PIR
Nodrošināts aprīkojums	Lietotāja rokasgrāmata Centre plate
Quantity per set	1
Product compatibility	To be completed with Renova frame

Papildinošs

Ierīces stiprinājums	Flush
Load type	Incandescent lamp 2200 W 230 V AC Halogen lamp 2000 W 230 V AC LED lamp 200 W 230 V AC Motor (single-phase) 1000 VA 230 V AC LV halogen lamps 1050 VA 12 V AC electronic transformer) LV halogen lamps 500 VA 12 V AC wound transformer)
Number of FUNCTION keys	1
Local signalling	Status 1 LED red)
Detection face	Frontal 8 m Lateral 8 m
Detection angle	180°
Number of outputs	1
Control type	Manual control Local control automatic load detection Remote control by auxiliary push-button
Light intensity adjustment	5...500 lux
Rated current	10 A 140 µF 10 A cos phi = 0,6
Time delay range	1...30 min
[Ue] rated operational voltage	230 V AC 50 Hz
Associated fuse rating	16 A
Colour tint	white RAL 9010)
Virsmas apdare	Glossy

Savienojumi - spaiļes	Skrūvju spaiļe
Number of loop terminals	2
Clamping connection capacity	1.5...2.5 mm ² solid 1.5...2.5 mm ² solid stranded
Shape of screw head	Pozidriv No 1 and combi
Tightening torque	0,5 N.m
Connected auxiliaries	Unlimited number of push-buttons 50 m
Material	PC (polycarbonate) GF10 FR casing Metal terminals ABS (acrylonitrile butadiene-styrene) central plate
Vadu konfigurācija	With neutral
Type of installation	Indoor installation
Montāžas atbalsts	Siena
Fixing mode	By screws
Embedding depth	29 mm
Depth	44 mm
Height	71 mm
Platums	71 mm
Neto svars	0,075 kg
Type of packing	Carton

Vide

Standartiem	EN 60730-2-7 EN 60669-2-1 EN 300-328 EN 301-489-17
Directives	2014/30/EU - electromagnetic compatibility 2014/35/EU - low voltage directive
Produktu sertifikāti	EAC CE FIMKO NEMKO VDE SEMKO
Apkārtējā gaisa temperatūra ekspluatācijai	5...35 °C
Apkārtējā gaisa temperatūra uzglabāšanai	-10...50 °C
IP degree of protection	IP20 IP21 with marking on visual parts

Iepakojšanas vienības

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	89,0 g
Package 1 Height	5,3 cm
Package 1 Width	8,0 cm
Package 1 Length	8,0 cm
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Weight	2,451 kg

Package 2 Height	15,0 cm
Package 2 Width	30,0 cm
Package 2 Length	40,0 cm

Offer Sustainability

Ilgtspējīgs piedāvājuma statuss	Green Premium izstrādājums
REACH regula	REACH deklarācija
ES RoHS direktīva	Atbilstīgs ES RoHS deklarācija
Nesatur dzīvsudrabu	Jā
Informācija par RoHS izņēmumiem	Jā
Ķīnas RoHS regula	Ķīnas RoHS deklarācija Produkts neietilpst Ķīnas RoHS ietvaros. Vietas deklarācijai informatīva nozīme.
Vides informācijas publiskošana	Produkta ietekme uz vidi
Cirkularitātes profils	Informācija par ekspluatācijas izbeigšanu
WEEE	Eiropas Savienības tirgū no šī produkta ir jāatbrīvojas, ievērojot noteiktu atkritumu savākšanas kārtību, un produkts nedrīkst nonākt sadzīves atkritumu tvertnēs.

Contractual warranty

Garantija	18 months
-----------	-----------