

SYSTEM TORES LED PC/PC 1200MM 5000LM 840 IP65 36W

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Luminous flux [lm]*:	5000
Colour temperature [K]:	4000
Material of the body:	PC
Colour of the body:	grey
Diffuser material:	PC
Diffuser type:	frozen
Mounting version:	surface, suspended
Dimensions (H/W/T/S) [mm]:	1200/85/80

CHARACTERISTICS

Tores LED PC is a lamp dedicated to LED technology. Designed from scratch, it introduces new solutions to improve light distribution and temperature balance. Its very good technical parameters guarantee the achievement of the required level of illumination and energy savings. The lamp has a number of improvements to make installation easier and faster, such as adjustable brackets that provide an installation tolerance of +/-50 mm. As standard, it is equipped with durable stainless steel (INOX) clips. The lamp has a high IP65 rating, and the lamp body and shade are UV resistant.

APPLICATION

Multifunctional surface-mounted LED lamp is designed for use in areas with high requirements for dust- and waterproofing. Particularly recommended for illuminating industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underpasses. The lamp is ideal for new lighting applications, as well as replacing traditional fluorescent fixtures with energy-efficient LED solutions.

SYSTEM TORES LED PC/PC 1200MM 5000LM 840 IP65 36W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	374166	LED lifespan L70B50 [h]:	103000
EAN:	5905963374166	LED lifespan L80B20 [h]:	65000
Light source:	LED module	LED lifespan L90B10 [h]:	32000
Rated power of the luminaire [W]:	36	Beam angle [°]:	120
Luminous flux [lm]:	5000	Diffuser material:	PC
Supply voltage [V]:	220-240	Diffuser type:	frozen
Frequency [Hz]:	50/60	Material of the body:	PC
Luminous efficacy [lm/W]:	139	Colour of the body:	grey
Energy efficiency class:	C	Dimensions (H/W/T/S) [mm]:	1200/85/80
Electrical protection class:	I	Ingress protection:	IP65
Colour temperature [K]:	4000	Mounting version:	surface, suspended
Colour rendering index:	>80	Working temperature [°C]:	from -20 to +40
SDCM:	≤ 3	Warranty [years]:	5

Card creation date: 09 February 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: