LUMELINK

CABLES TIES

Material: Cable ties are made from high quality Nylon (Polyamide 6.6)
Resistance: Good resistance to bases, oils, greases, oil derivatives, chloride solvents.
Working temperature: -40℃~85℃
Black colour: UV resistant

L - Length
W - Width
D - Bundle diameter

Product name	Product code	Colour	Dimensions		Minimum bundle diameter [mm]	Maximum bundle diameter [mm]	Minimum tensile strength [N]
			Length [mm]	Width [mm]			
Cable tie 100x2.5	CT-PA-100/2.5-N	White	100±3	2.5±0.2	3.00	20.50	80
Cable tie 150x3.6	CT-PA-150/3.6-N	White	150±3	3.6±0.2	3.50	36.00	180
Cable tie 200x4.8	CT-PA-200/4.8-N	White	200±3	4.8±0.2	3.50	49.50	230
Cable tie 200x4.8	CT-PA-200/4.8-B	Black	200±3	4.8±0.2	3.50	49.50	230
Cable tie 250x4.8	CT-PA-250/4.8-N	White	250±3	4.8±0.2	3.50	65.00	230
Cable tie 250x4.8	CT-PA-250/4.8-B	Black	250±3	4.8±0.2	3.50	65.00	230
Cable tie 300x4.8	CT-PA-300/4.8-N	White	300±3	4.8±0.2	3.50	81.00	230
Cable tie 300x4.8	CT-PA-300/4.8-B	Black	300±3	4.8±0.2	3.50	81.00	230
Cable tie 380x7.6	CT-PA-380/7.6-N	White	380±5	7.6±0.3	8.50	108.00	540
Cable tie 380x7.6	CT-PA-380/7.6-B	Black	380±5	7.6±0.3	8.50	108.00	540
Cable tie 550x9.0	CT-PA-550/9.0-N	White	550±6	8.8±0.4	8.50	163.50	800
Cable tie 550x9.0	CT-PA-550/9.0-B	Black	550±6	8.8±0.4	8.50	163.50	800

RoHS LVD UV CE HF

Distributed by: ENERGY GROUP LV SIA, Lubanas street 76, Riga, Latvia, LV-1073, +371 67281291